

PE rainwater storage tank Aqua terne 204

Equipment:



- with or without integrated filter (for roof areas up to 150m²)
- turret, lid, overflow and calmed inlet included



Operation:

The tank is especially designed for storing rainwater and is equipped with everything that is necessary to achieve an excellent water quality and keep maintenance to a minimum. It is available in different sizes: 3 500 I, 25 000 I and 52500 I. Due to its small weight it is easy to install. The rainwater storage tank has an integrated 4 step filtration system.

Item No	Volume [l]	Total height [mm]	Height of tank [mm]	Total length [mm]	Diameter [mm]	Weight [kg]
G 12026	5,000*	2850	2024	2330	2024	365
G 12029	8,500*	2850	2024	3670	2024	560
G 12030	12,500	2850	2024	5020	2024	755
G 12033	16,000	2850	2024	6360	2024	955
G 12035	19,500	2850	2024	7690	2024	1145
G 12036	23,500	2850	2024	9030	2024	1340
G 12037	27,000	2850	2024	9980	2024	1460

^{*}Tanks is available with integrated filter (different item no.)





The rainwater storage tank has an integrated 4 step filtration system. In that way you get an excellent water quality and the tank may have to be cleaned once every 10 – 15 years.




The fine filter (accessory) avoids dirt-particles from entering the tank. The filter is self-cleaning and can be easily taken out for maintenance. (1)



Calmed inlet

Very fine dust-particles are sinking down to the bottom of the tank. The design of the inlet avoids swirling up particles. (2)



Overflow siphon



Very light fine particles build a swimming layer. This layer is automatically taken away

each time the tank overflows. In case of a connection to a combined sewer the siphon avoids the entering of rodents and odour. (3)



Floating extraction (accessory)

The floating extraction allows the pump to suck the water just under the water surface where it is cleanest. An additional fine filter will protect the suction pump. (4)

Car duty up to 5 t if using a concrete lid and frame (available as accessories)



